

S84/86 **NX**



Intelligence • Reliability • Versatility

INTELLIGENCE

- Pre-installed auto-switch competitive printer language emulations
- Full color 3.5" LCD display with intuitive menu and easy navigation
- On-board instructional videos for training and maintenance

RELIABILITY

- Tool-free maintenance for print head and front-access roller replacement
- Reinforced aluminum construction print head mechanism and larger hinges for strength and durability
- Remote management with SATO Online Services (SOS)

VERSATILITY

- Application Enabled Printing (AEP) allowing PC-free operation with interactive controls and interface
- Shortcuts provide user defined quick access to frequently performed operations
- UHF RFID (S84NX only) option for writing, reading, and verifying tags prior to printing



GENERAL SPECIFICATIONS / S84NX - S86NX

PRODUCT SPECIFICATIONS		S84NX			S86NX		
Print Resolution		203dpi (8 dots/mm)	305dpi (12 dots/mm)	609dpi (24 dots/mm)	203dpi (8 dots/mm)	305dpi (12 dots/mm)	
Print Speed		16ips (406.4mm/sec)	14ips (355.6mm/sec)	6ips (15.4 2mm/sec)	14ips (355.6mm/sec)	12ips (304.8mm/sec)	
Print Area	Max Width	4.1" (104mm)			6.6" (167.5mm)		
	Max Length	98.43" (2500mm)	59.06" (1500mm)	15.75" (400mm)	98.43" (2500mm)	59.06" (1500mm)	
Media Size (with liner)	Continuous	Width	0.51" to 5.16" (13 to 131mm)			2.13" to 7.09" (54 to 180mm)	
		Length	0.35" to 98.54" (9 to 2503mm)	0.35" to 59.17" (9 to 1503mm)	0.35" to 15.87" (9 to 403mm)	0.24" to 98.54" (9 to 2503mm)	0.35" to 59.17" (9 to 1503mm)
	Dispense	Width	0.51" to 5.16" (13 to 131mm)			2.13" to 7.09" (54 to 180mm)	
		Length	Thermal Transfer Model: 0.51" to 14.13" (13 to 359mm) Direct Thermal Model: 0.71" to 14.13" (18 to 359mm)				
Ribbon	Length / width	1476.4ft. (450m) when width is less than 1.56" (39.5mm) 1968.5 ft. (600m) when width is equal or more than 1.55" (39.5mm)			1968.5 ft. (600m) when ribbon width is 2.32" (59mm) to 6.96" (177mm)		
	Roll diameter	4.25" (108mm)					
	Core	Core diameter: Ø 1" (25.4mm)					
	Wind direction	Face-in/out, No Setting Change Required					
	Ribbon Tension	Clutch-Free Electronic Control System					
Dimensions		W 9.65" (245mm) x D 16.06" (408mm) x H 11.81" (300mm)			W 9.65" (245 mm) x D 16.42" (417mm) x H 11.81" (300mm)		
Weight		Thermal Transfer Model: 31lbs (14.1kg) Direct Thermal Model: 28lbs (12.7kg)			Thermal Transfer Model: 34lbs (15.5kg) Direct Thermal Model: 30.8lbs (14.0kg)		

PRINTING SPECIFICATIONS	
Method	Direct Thermal / Thermal Transfer or Direct Thermal Only
Mode	Continuous, Dispense

MEDIA SPECIFICATIONS	
Sensor Type	Top Sensor, Adjustable Transmissive Sensor for Gap, Adjustable Reflective Sensor for Black Mark, Paper Out, Ribbon Near-End/Out, Label Near-End
Media Type	Die Cut Labels, Paper or Synthetic Stock
Media	
Thickness (Label & Liner)	0.002" to 0.012" (0.05 - 0.31mm)
Wind	Face-in / Face-out. No Setting Change Required
SATO Genuine Consumables	For maximum print quality and optimum use, SATO recommends the use of SATO genuine consumables.

CONNECTIVITY	
Standard	2x USB 2.0 Type-A (host) Front and Rear, Ethernet 10/100 Mbps / DHCP / Protocol: TCP/IP, LPR, FTP, TELNET, SNTP, RS232C Standard (XON/XOFF,RTS/CTS), DSUB25 pin (female)
Optional Wireless LAN Kit (Internal)	Wireless LAN, WiFi Certified, WiFi Direct, IEEE 802.11 a/ b/g/n/ac Dual Band (2.4GHz, 5GHz), Security: WEP, WPA, WPA2, Dynamic WEP, DHCP Option 81.

OPTIONS	
	WLAN Kit (specifics above), RFID Kit (S84NX Only), UHF (920MHz), ISO/IEC 18000-6 Type C Gen 2 For more information about qualified RFID inlays and labels please contact SATO.

MEMORY & PROCESSING	
Dual CPU	CPU1: 2 GB Flash, 256MB RAM CPU2: 4 MB Flash, 64MB RAM User Registration Area 576MB Receive Buffer 2.95MB

USER-FRIENDLY SUPPORT TOOLS	
Display Panel	3.5" Full-Color LCD 9 buttons control keys
Status LCD	Blue / Red
Audible Alerts	Sound beep (4 volume settings)
Emulation	Auto Detect - SBPL®, SZPL®, SIPL®, SDPL®, (pre-installed), XML, AEP
Rotation	Character data rotation: 0°, 90°, 180°, 270° / Barcode rotation: 0°, 90°, 180°, 270°
Self Diagnosis	Thermal head check, Ribbon end detection, Test print, Head Lift detection, Auto Sensor Calibration
Remote Settings / Maintenance	Web Browser, SATO All-in-One Printer Utilities, SOS, SNMPv3
Additional Functions	Simple Standalone Mode, Multi Language support LCD message (31 Languages), USB Memory, clone functionality and firmware updates, Status return, Micro Label Printing, User guidance videos in display, Custom videos, Energy saving, SOS (SATO Online-services), Direct PDF printing, RTC- (Real-time Clock)
Drivers	Windows, Linux, SAP, MAC OS

FONT SPECIFICATIONS	
Internal Fonts	7 bitmap SATO fonts, 30 scalable SATO fonts, Multi-national language support (47 languages/Unicode), Single and double byte fonts (Korean, Chinese, Japanese)

BARCODE SYMBOLOGIES SPECIFICATIONS	
Barcodes	
Linear	Code 39, Code 93, Code 128, CODABAR (NW-7), EAN 8/13, GS1 DataBar™, GS1-128 (UCC/EAN 128), Interleaved 2/5, Industrial 2/5, JAN 8/13, Matrix 2/5, MSI, Bookland, POSTNET™, UPC-A/E Intelligent Mail Barcode
2D Symlogies	PDF417, Micro PDF, Maxi Code, GS1 Data Matrix, QR Code, Micro QR Code, Security QR, Composite Symlogies, Aztec

OPERATING CHARACTERISTICS	
Electrical Requirements	Universal Auto-ranging Power Supply, 100-240VAC +/- 10%, 50/60Hz
Standards & Agency Approvals	IEC 60950, CE Marking, NEMKO-GS, cMETus, UL60950-1, CSA C22.2, EN 60950-1, FCC, ICES-003, NMB-003, RCM, CCC, SRRC, KC, ROHS compliant
Environment	
Operating	23° - 104° F (-5° to 40 °C) / 15 - 85% RH (without condensation)
Storage	-4° - 140° F (-20° to 60 °C) / 15 - 90 % RH (without condensation)

SATO AMERICA 14125 South Bridge Circle

CORPORATE

Charlotte, NC 28273
Phone: (704) 644-1650

sales-sallc@sato-global.com

LABEL MANUFACTURING, SERVICE & SALES

UNITED STATES MEXICO CENTRAL AMERICA
CANADA CARIBBEAN

©2024 SATO America. All rights Reserved. Rev A • Any unauthorized reproduction of this content, in part or whole, is strictly prohibited • SATO is a registered trademark of SATO Corporation and its subsidiaries in Japan, the U.S. and other countries. All other trademarks are the property of their respective owners.

www.satoamerica.com/S84-S86NX